



## SUBTRACTIVE DEVELOPER

Boiling Point °C	200-206	Specific Gravity (H <sub>2</sub> O = 1)	1.02
Vapor Pressure (mm Hg.)	°C	Melting Point	
Vapor Density (AIR = 1)		Evaporation Rate (Butyl Acetate = 1)	LESS THAN 1
Solubility in Water APPRECIABLE			
Appearance and Odor SLIGHTLY TURBID SOLUTION, LOW ODOR			

## Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used)	NONE	Flammable Limits	N/A	LEL	N/A	UEL	N/A
Extinguishing Media NONE							
Special Fire Fighting Procedures NONE							
Unusual Fire and Explosion Hazards NONE							

(Reproduce locally)

OSHA 174, Sept. 1985

## Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (Materials to Avoid) NONE			
Hazardous Decomposition or Byproducts NONE			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	NONE

## Section VI - Health Hazard Data

**SUBTRACTIVE DEVELOPER**

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
Health Hazards ( <i>Acute and Chronic</i> )			
Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
Signs and Symptoms of Exposure <b>SLIGHT SKIN IRRITATION MAY OCCUR AFTER PROLONGED CONTACT.</b>			
Medical Conditions Generally Aggravated by Exposure			
Emergency and First Aid Procedures <b>AFTER PROLONGED EXPOSURE, FLUSH SKIN WITH WATER</b>			

**Section VII - Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled	<b>SOAK UP WITH ABSORBANT</b>
Waste Disposal Method	<b>FLUSH WITH WATER</b>
Precautions to Be taken in Handling and Storing	<b>NONE</b>
Other Precautions	<b>NONE</b>

**Section VIII - Control Measures**

Respiratory Protection ( <i>Specify Type</i> )		
Ventilation	Local Exhaust <b>PREFERABLE</b>	Special <b>N/A</b>
	Mechanical ( <i>General</i> ) <b>ACCEPTABLE FOR PROLONGED</b>	Other <b>N/A</b>
Protective Gloves	<b>CONTACT</b>	Eye Protection
Other Protective Clothing or Equipment	<b>N/A</b>	
Work/Hygienic Practices		